



L7R122

Power Handling
600 Watts RMS / 1200 Watts Max.

Technical Specifications

Impedance	Zn	2 + 2 Ohms
Voice Coil Diameter	Ø	50 mm
Max. Linear Excursion	Xmax	+/- 16,25 mm
Cone Area	Sd	645 cm ²
Moving Mass	Mms	260,68 g
DC Resistance	Re	1,8 + 1,8 Ohms
Resonance Frequency	Fs	30,1 Hz
Mechanical Q-Factor	Qms	10,29
Electrical Q-Factor	Qes	0,67
Total Q-Factor	Qts	0,63
Equivalent Air Volume	VAS	67,4 L
VC Inductance	Le	6,514 mH
Flux Density	B/L	22,39 N/A
Efficiency 1W/1m	SPL	86,7 dB

Dual Voice Coil
Subwoofer 30 cm

Recommended Enclosure

Ported Box	
Vented Volume:	92 L
Port Area:	258 cm ²
Port Length:	37 cm

Recommended Enclosure

Ported Box	
Vented Volume:	49,6 L
Port Area:	217 cm ²
Port Length:	57 cm

Mechanical Components

- Steel Basket
- Polypropylene Cone
- Santoprene Surround
- Polypropylene Dustcap
- Single Spider
- Y30 Magnet 76 oz (2.155 g)
- Magnet Size: Ø160 x 30 mm
- Polyimide Voice Coil Former

Dimensions & Weight

External Diameter:	321 mm
Mounting Diameter:	281 mm
Mounting Depth:	174 mm
Shipping Weight:	10,5 kg

