



S10L72-11

**Dual Voice Coil
Subwoofer 25 cm**

Power Handling
600 Watts RMS / 1200 Watts Max.

Technical Specifications

Impedance	Zn	2 x 2 Ohms
Voice Coil Diameter	Ø	50 mm
Max. Linear Excursion	Xmax	+/- 14 mm
Cone Area	Sd	439 cm ²
Moving Mass	Mms	169,7 g
DC Resistance	Re	2 x 2 Ohms
Resonance Frequency	Fs	34,7 Hz
Mechanical Q-Factor	Qms	6,15
Electrical Q-Factor	Qes	0,45
Total Q-Factor	Qts	0,42
Equivalent Air Volume	VAS	33,2 L
Flux Density	B/L	16,19 N/A
Efficiency 1W/1m	SPL	86,8 dB

Recommended Enclosure

Ported Box	
Vented Volume:	49,5 L
Port Area:	202 cm ²
Port Length:	45 cm

Recommended Enclosure

Ported Box	
Vented Volume:	35,4 L
Port Area:	185 cm ²
Port Length:	50 cm

Mechanical Components

- Diecast Aluminium Basket
- Polypropylene Cone
- Santoprene Surround
- Polypropylene Dustcap
- Single Spider
- Polyimide Voice Coil Former

Dimensions & Weight

External Diameter:	273 mm
Mounting Diameter:	237 mm
Mounting Depth:	159 mm
Shipping Weight:	10,6 kg

